



Product Service

# Attestation of Conformity

No. N8A 094747 0119 Rev. 00

**Holder of Attestation:** **Xinsu Global Electronic Co., Limited**  
Unit 2508A, 25/F Bank Of America Tower, 12 Harcourt Road  
Central  
HONG KONG

**Product:** **Switching power supply unit**  
**(SWITCHING POWER SUPPLY / CHARGER)**

This Attestation of Conformity is issued on a voluntary basis according to the Low Voltage Directive 2014/35/EU relating to electrical equipment designed for use within certain voltage limits. It confirms that the listed equipment complies with the principal protection requirements of the directive and is based on the technical specifications applicable at the time of issuance. It refers only to the particular sample submitted for conformity assessment. For details see: [www.tuvsud.com/ps-cert](http://www.tuvsud.com/ps-cert)

**Test report no.:** 652102215901

**Date,** 2023-03-02

( Rickyet Wang )

Page 1 of 2

This Attestation does not replace the regulatory EU Declaration of Conformity (DoC) and does not allow for CE marking. After preparation of the necessary documentation and establishing compliance to requirements of all applicable directives, the manufacturer may sign a DoC and apply the CE marking. The DoC is issued under the sole responsibility of the manufacturer.



TUV®



Product Service

# Attestation of Conformity

No. N8A 094747 0119 Rev. 00

**Model(s):** XSGxxxxxyzz, XSGxxxxxy, XSEC050yyyyzz, XSEC050yyyy, XSExxxxxy, XSExxxxxyEU (xxx=042-365, stands for rated output voltage from 4.2VDC to 36.5VDC; yyyy=0100-3000, stands for rated output current from 0.1A to 3.0A; zz=EU or UK stands for direct plug-in plug type; EU means Europe plug, UK means Britain plug.)

**Brand:** Xinsu Global



## Parameters:

Rated Input: 100-240VAC, 50/60Hz, 0.6A Max

Rated Output: See below table for details

Protection Class: II

Degree of Protection: IP20

| Model No.                                      | Rated output voltage (VDC) | Rated output current (A) | Max. rated output power (W) |
|--|----------------------------|--------------------------|-----------------------------|
| XSEC050yyyyzz, XSEC050yyyy,                    | 5.0                        | 0.1-3.0                  | 15.0                        |
| XSGxxxxxyzz, XSGxxxxxy, XSExxxxxy, XSExxxxxyEU | 4.2-5.0                    | 0.1-3.0                  | 15.0                        |
|  | 5.1-6.0                    | 0.1-2.5                  | 15.0                        |
|  | 6.1-7.9                    | 0.1-2.0                  | 14.0                        |
|  | 8.0-9.0                    | 0.1-1.8                  | 16.2                        |
|  | 9.1-11.5                   | 0.1-1.6                  | 15.0                        |
|  | 11.6-16.8                  | 0.1-1.5                  | 18.0                        |
|  | 16.9-18.0                  | 0.1-1.0                  | 18.0                        |
|  | 18.1-20.0                  | 0.1-0.9                  | 18.0                        |
|  | 20.1-36.5                  | 0.1-0.85                 | 18.25                       |

**Tested according to:** EN 62368-1:2014/A11:2017

Page 2 of 2

This Attestation does not replace the regulatory EU Declaration of Conformity (DoC) and does not allow for CE marking. After preparation of the necessary documentation and establishing compliance to requirements of all applicable directives, the manufacturer may sign a DoC and apply the CE marking. The DoC is issued under the sole responsibility of the manufacturer.

