



Product Service

# Attestation of Conformity

No. N8A 094747 0068 Rev. 00

**Holder of Certificate:** **Xinsu Global Electronic Co., Limited**  
Unit 2508A, 25/F Bank Of America Tower, 12 Harcourt Road  
Central  
HONG KONG

**Product:** **Switching power supply unit  
(SWITCHING POWER SUPPLY/CHARGER)**

This Attestation of Conformity is issued on a voluntary basis according to the Low Voltage Directive 2014/35/EU relating to electrical equipment designed for use within certain voltage limits. It confirms that the listed equipment complies with the principal protection requirements of the directive and is based on the technical specifications applicable at the time of issuance. It refers only to the particular sample submitted for testing and certification. For details see: [www.tuvsud.com/ps-cert](http://www.tuvsud.com/ps-cert)

**Test report no.:** 652102008601

**Date,** 2021-05-26

( Ricky Wang )

Page 1 of 2

After preparation of the necessary technical documentation as well as the EU declaration of conformity the required CE marking can be affixed on the product. The declaration of conformity is issued under the sole responsibility of the manufacturer. Other relevant EU-directives have to be observed.



Product Service

# Attestation of Conformity

No. N8A 094747 0068 Rev. 00

**Model(s):** XSGxxxxxyzz L3, XSGxxxxxy L3,  
 XSExxxxxy L3, XSExxxxxyzz L3,  
 XSECxxxxxyzz L3, XSECxxxxxy L3  
 (xxx=042-480, indicates rated output voltage from  
 4.2VDC to 48.0VDC; yyyy=0010-4000, indicates rated  
 output current from 0.01A to 4.0A; zz=EU or UK,  
 indicates different AC plug: EU=European plug,  
 UK=Britain plug)

**Brand:** Xinsu Global



## Parameters:

Rated Input: 100-240VAC, 50/60Hz, 0.6A Max

Rated Output: See below table for details

Protection Class: II

Degree of Protection: IP20

Model	Rated output voltage (VDC)	Rated output current (A)	Max. rated output power (W)
XSGxxxxxyzz L3, XSGxxxxxy L3, XSExxxxxy L3, XSExxxxxyzz L3, XSECxxxxxyzz L3, XSECxxxxxy L3	4.2-6.9	0.01-4.00	20.0
	7.0-9.0	0.01-3.00	22.5
	10.0-12.0	0.01-2.50	30.0
	12.1-12.6	0.01-2.47	30.0
	12.8-17.0	0.01-2.34	30.0
	18.1-20.0	0.01-1.50	30.0
	21.0-36.0	0.01-1.42	30.0
	36.1-48.0	0.01-0.80	30.0

**Tested**

EN 62368-1:2014/A11:2017

**according to:**

Page 2 of 2

After preparation of the necessary technical documentation as well as the EU declaration of conformity the required CE marking can be affixed on the product. The declaration of conformity is issued under the sole responsibility of the manufacturer. Other relevant EU-directives have to be observed.