



Product Service

Attestation of Conformity

No. N8A 094747 0019 Rev. 01**Holder of Attestation: Xinsu Global Electronic Co., Limited**Unit 2508A, 25/F Bank Of America Tower, 12 Harcourt Road
Central
HONG KONG**Product: Switching power supply unit
(SWITCHING POWER SUPPLY)**

This Attestation of Conformity is issued on a voluntary basis according to the Low Voltage Directive 2014/35/EU relating to electrical equipment designed for use within certain voltage limits. It confirms that the listed equipment complies with the principal protection requirements of the directive and is based on the technical specifications applicable at the time of issuance. It refers only to the particular sample submitted for conformity assessment. For details see: www.tuvsud.com/ps-cert

Test report no.: 652101801103**Date,** 2025-08-22

(Rickyet Wang)

Page 1 of 2

This Attestation does not replace the regulatory EU Declaration of Conformity (DoC) and does not allow for CE marking. After preparation of the necessary documentation and establishing compliance to requirements of all applicable directives, the manufacturer may sign a DoC and apply the CE marking. The DoC is issued under the sole responsibility of the manufacturer.



Product Service

Attestation of Conformity

No. N8A 094747 0019 Rev. 01

Model(s):

XSGxxxxxxx L1, XSGxxxxxxxEU L1,
 XSExxxxxxx L1, XSExxxxxxxzz L1,
 XSECxxxxxxx L1, XSECxxxxxxxzz L1,
 (xxx=030-480, stands for the rated output voltage
 3.0VDC-48.0VDC, in step of 0.1V; yyyy=0100-5000,
 stands for the rated output current 0.10A-5.00A, in
 step of 0.01A; zz=EU or UK, stands for different
 plug type, EU stands for Europe plug, UK stands
 for British plug.)

Brand:

Xinsu Global



Parameters:

Rated Input: 100-240VAC, 50/60Hz, 1.3A Max
 Rated Output: See below table for details
 Protection Class: II
 Degree of Protection: IP20

Model No.	Rated output voltage (VDC)	Rated output current (A)	Maximum rated output power (W)
XSGxxxxxxxEU L1, XSGxxxxxxx L1, XSExxxxxxx L1, XSECxxxxxxx L1, XSECxxxxxxxzz L1, XSExxxxxxxzz L1	3.0-7.9	0.10-5.00	25.0
	8.0-9.0	0.10-4.00	36.0
	9.1-12.6	0.10-3.00	37.8
	12.7-17.0	0.10-2.50	39.6
	17.1-30.0	0.10-2.00	40.0
	30.1-48.0	0.10-1.32	40.0

Tested according to:

EN IEC 61558-1:2019
 EN 61558-2-16:2009/A1:2013

Page 2 of 2

This Attestation does not replace the regulatory EU Declaration of Conformity (DoC) and does not allow for CE marking. After preparation of the necessary documentation and establishing compliance to requirements of all applicable directives, the manufacturer may sign a DoC and apply the CE marking. The DoC is issued under the sole responsibility of the manufacturer.