



FCC Part 15 SDOC

Supplier's Declaration of Conformity

This Certificate of Conformity is hereby issued to the product designated below:

Certificate No. : 25EP060200F02
Report No. : EP25060200F02
Date Issue. : 2025-10-15
Applicant's name : Xinsu Global Electronic Co., Limited
Address : Unit 2508A, 25/F Bank Of America Tower, 12 Harcourt Road, Central,
HONG KONG
Manufacturer's name : Xinsu Global Electronic Co., Limited
Address : Unit 2508A, 25/F Bank Of America Tower, 12 Harcourt Road, Central,
HONG KONG
Product Description : SWITCHING POWER SUPPLY/CHARGER
Model(s)/Type References : XSGxxxxxyUS L1, XSGxxxxxy L1, XSExxxxxy L1,
XSECxxxxxy L1, XSECxxxxxyUS L1, XSExxxxxyUS L1,
XSGxxxxxyUS, XSGxxxxxy, XSExxxxxy, XSECxxxxxy,
XSECxxxxxyUS, XSExxxxxyUS
(xxx and yyyy are variables, see appendix for details)
Parameters : Input: 100-240VAC, 50/60Hz, 1.3A Max
Output: See appendix for details
Standard(s) : FCC Part 15 Subpart B
ANSI C63.4:2014


The device bearing the trade name and model specified above has been shown to comply with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified. (Refer to Test Report if any modifications were made for compliance).

This certificate of conformity is based on a single evaluation of the submitted sample(s) of the above mentioned product. It does not imply an assessment of the whole production have to be observed.

Approved By

Eric Liu

Director of engineering department





FCC Part 15 SDOC

Supplier's Declaration of Conformity

Appendix of Certificate No.: 25EP060200F02

Model list:

Model No.	Rated output voltage (VDC)	Rated output current (A)	Maximum rated output power (W)	Transformer
XSGxxxxxyUS L1, XSGxxxxxy L1,	3.0-7.9	0.10-5.00	25.0	TR-036B-05A
XSExxxxxy L1, XSECxxxxxy L1,	8.0-9.0	0.10-4.00	36.0	TR-036B-12A
XSECxxxxxyUS L1, XSExxxxxyUS L1,	9.1-12.6	0.10-3.00	37.8	
XSGxxxxxyUS, XSGxxxxxy,	12.7-17.0	0.10-2.50	39.6	
XSExxxxxy, XSECxxxxxy,	17.1-30.0	0.10-2.00	40.0	TR-036B-24A
XSECxxxxxyUS, XSExxxxxyUS	30.1-48.0	0.10-1.32	40.0	TR-036B-36A
Remark: xxx=030-480, stands for the rated output voltage 3.0VDC-48.0VDC, in step of 0.1V; yyy=0100-5000, stands for the rated output current 0.10A-5.00A, in step of 0.01A				

