



A P P R O V A L S ®

## Certificate of Conformity/Approval

**Certificate No.:** SAA-211085-EA

**Certificate Holder:** Xinsu Global Electronic Co., Limited  
Unit 2508A, 25/F Bank of America Tower  
12 Harcourt Road  
Central  
Hong Kong

**Regulatory Definition:** Power supply or charger

**Product Description:** Switching Power Supply

**Standard/s:** AS/NZS 62368.1:2022

**Condition/s:** For use with audio/video, information or  
communication technology equipment only.

**Approval Marks:** RCM (In accordance with AS/NZS 4417 and EESS requirements)  
and  
SAA-211085-EA (In accordance with NSW legislative requirements)

**Initial Issue Date:** 23 June 2021

**Expiry Date:** 11 March 2031

*R. A. Hill*

For and on Behalf of  
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065, RECS accreditation under the Queensland Government legislative requirements and REAS accreditation under the NSW Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and Certificate verification, go to:

[www.saaapprovals.com.au](http://www.saaapprovals.com.au)



[www.jas-anz.org/register](http://www.jas-anz.org/register)



Issued: 11-03-26 211085  
Renewed Page 1 of 45



A P P R O V A L S ®

## Certificate of Conformity/Approval

| Model           | Trade Name   | Rating/Marking                                                                         |
|-----------------|--------------|----------------------------------------------------------------------------------------|
| XSG1202500 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 12.0Vdc 2.5A 30.0W<br>ta:35°C, Class II |
| XSG1202500AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 12.0Vdc 2.5A 30.0W<br>ta:35°C, Class II |
| XSG0420500 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 4.2Vdc 0.5A 2.1W<br>ta:35°C, Class II   |
| XSG0420500AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 4.2Vdc 0.5A 2.1W<br>ta:35°C, Class II   |
| XSG0421000 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 4.2Vdc 1.0A 4.2W<br>ta:35°C, Class II   |
| XSG0421000AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 4.2Vdc 1.0A 4.2W<br>ta:35°C, Class II   |
| XSG0421500 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 4.2Vdc 1.5A 6.3W<br>ta:35°C, Class II   |
| XSG0421500AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 4.2Vdc 1.5A 6.3W<br>ta:35°C, Class II   |
| XSG0422000 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 4.2Vdc 2.0A 8.4W<br>ta:35°C, Class II   |
| XSG0422000AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 4.2Vdc 2.0A 8.4W<br>ta:35°C, Class II   |

R. A. Nill


For and on Behalf of  
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065, RECS accreditation under the Queensland Government legislative requirements and REAS accreditation under the NSW Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and Certificate verification, go to:

[www.saaapprovals.com.au](http://www.saaapprovals.com.au)

JAS-ANZ



[www.jas-anz.org/register](http://www.jas-anz.org/register)



Issued: 11-03-26 211085  
Renewed Page 2 of 45



A P P R O V A L S ®

## Certificate of Conformity/Approval

| Model           | Trade Name   | Rating/Marking                                                                        |
|-----------------|--------------|---------------------------------------------------------------------------------------|
| XSG0422500 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 4.2Vdc 2.5A 10.5W<br>ta:35°C, Class II |
| XSG0422500AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 4.2Vdc 2.5A 10.5W<br>ta:35°C, Class II |
| XSG0423000 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 4.2Vdc 3.0A 12.6W<br>ta:35°C, Class II |
| XSG0423000AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 4.2Vdc 3.0A 12.6W<br>ta:35°C, Class II |
| XSG0424000 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 4.2Vdc 4.0A 16.8W<br>ta:35°C, Class II |
| XSG0424000AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 4.2Vdc 4.0A 16.8W<br>ta:35°C, Class II |
| XSG0500500 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 5.0Vdc 0.5A 2.5W<br>ta:35°C, Class II  |
| XSG0500500AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 5.0Vdc 0.5A 2.5W<br>ta:35°C, Class II  |
| XSG0501000 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 5.0Vdc 1.0A 5.0W<br>ta:35°C, Class II  |
| XSG0501000AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 5.0Vdc 1.0A 5.0W<br>ta:35°C, Class II  |

R. A. Nill

For and on Behalf of  
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065, RECS accreditation under the Queensland Government legislative requirements and REAS accreditation under the NSW Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and Certificate verification, go to:

[www.saaapprovals.com.au](http://www.saaapprovals.com.au)



[www.jas-anz.org/register](http://www.jas-anz.org/register)



Issued: 11-03-26 211085  
Renewed Page 3 of 45



A P P R O V A L S ®

## Certificate of Conformity/Approval

| Model           | Trade Name   | Rating/Marking                                                                        |
|-----------------|--------------|---------------------------------------------------------------------------------------|
| XSG0501200 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 5.0Vdc 1.2A 6.0W<br>ta:35°C, Class II  |
| XSG0501200AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 5.0Vdc 1.2A 6.0W<br>ta:35°C, Class II  |
| XSG0501500 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 5.0Vdc 1.5A 7.5W<br>ta:35°C, Class II  |
| XSG0501500AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 5.0Vdc 1.5A 7.5W<br>ta:35°C, Class II  |
| XSG0502000 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 5.0Vdc 2.0A 10.0W<br>ta:35°C, Class II |
| XSG0502000AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 5.0Vdc 2.0A 10.0W<br>ta:35°C, Class II |
| XSG0502100 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 5.0Vdc 2.1A 10.5W<br>ta:35°C, Class II |
| XSG0502100AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 5.0Vdc 2.1A 10.5W<br>ta:35°C, Class II |
| XSG0502500 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 5.0Vdc 2.5A 12.5W<br>ta:35°C, Class II |
| XSG0502500AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 5.0Vdc 2.5A 12.5W<br>ta:35°C, Class II |

R. A. Nill

For and on Behalf of  
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065, RECS accreditation under the Queensland Government legislative requirements and REAS accreditation under the NSW Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and Certificate verification, go to:

[www.saaapprovals.com.au](http://www.saaapprovals.com.au)



[www.jas-anz.org/register](http://www.jas-anz.org/register)



Issued: 11-03-26 211085  
Renewed Page 4 of 45



A P P R O V A L S ®

## Certificate of Conformity/Approval

| Model           | Trade Name   | Rating/Marking                                                                        |
|-----------------|--------------|---------------------------------------------------------------------------------------|
| XSG0503000 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 5.0Vdc 3.0A 15.0W<br>ta:35°C, Class II |
| XSG0503000AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 5.0Vdc 3.0A 15.0W<br>ta:35°C, Class II |
| XSG0503500 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 5.0Vdc 3.5A 17.5W<br>ta:35°C, Class II |
| XSG0503500AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 5.0Vdc 3.5A 17.5W<br>ta:35°C, Class II |
| XSG0504000 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 5.0Vdc 4.0A 20.0W<br>ta:35°C, Class II |
| XSG0504000AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 5.0Vdc 4.0A 20.0W<br>ta:35°C, Class II |
| XSG0600500 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 6.0Vdc 0.5A 3.0W<br>ta:35°C, Class II  |
| XSG0600500AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 6.0Vdc 0.5A 3.0W<br>ta:35°C, Class II  |
| XSG0600600 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 6.0Vdc 0.6A 3.6W<br>ta:35°C, Class II  |
| XSG0600600AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 6.0Vdc 0.6A 3.6W<br>ta:35°C, Class II  |

R. A. Nill

For and on Behalf of  
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065, RECS accreditation under the Queensland Government legislative requirements and REAS accreditation under the NSW Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and Certificate verification, go to:

[www.saaapprovals.com.au](http://www.saaapprovals.com.au)



[www.jas-anz.org/register](http://www.jas-anz.org/register)



Issued: 11-03-26 211085  
Renewed Page 5 of 45



A P P R O V A L S ®

## Certificate of Conformity/Approval

| Model           | Trade Name   | Rating/Marking                                                                        |
|-----------------|--------------|---------------------------------------------------------------------------------------|
| XSG0601000 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 6.0Vdc 1.0A 6.0W<br>ta:35°C, Class II  |
| XSG0601000AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 6.0Vdc 1.0A 6.0W<br>ta:35°C, Class II  |
| XSG0601500 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 6.0Vdc 1.5A 9.0W<br>ta:35°C, Class II  |
| XSG0601500AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 6.0Vdc 1.5A 9.0W<br>ta:35°C, Class II  |
| XSG0602000 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 6.0Vdc 2.0A 12.0W<br>ta:35°C, Class II |
| XSG0602000AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 6.0Vdc 2.0A 12.0W<br>ta:35°C, Class II |
| XSG0602500 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 6.0Vdc 2.5A 15.0W<br>ta:35°C, Class II |
| XSG0602500AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 6.0Vdc 2.5A 15.0W<br>ta:35°C, Class II |
| XSG0603000 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 6.0Vdc 3.0A 18.0W<br>ta:35°C, Class II |
| XSG0603000AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 6.0Vdc 3.0A 18.0W<br>ta:35°C, Class II |

R. A. Nill

For and on Behalf of  
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065, RECS accreditation under the Queensland Government legislative requirements and REAS accreditation under the NSW Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and Certificate verification, go to:

[www.saaapprovals.com.au](http://www.saaapprovals.com.au)



[www.jas-anz.org/register](http://www.jas-anz.org/register)



Issued: 11-03-26 211085  
Renewed Page 6 of 45



A P P R O V A L S ®

## Certificate of Conformity/Approval

| Model           | Trade Name   | Rating/Marking                                                                        |
|-----------------|--------------|---------------------------------------------------------------------------------------|
| XSG0603500 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 6.0Vdc 3.5A 21.0W<br>ta:35°C, Class II |
| XSG0603500AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 6.0Vdc 3.5A 21.0W<br>ta:35°C, Class II |
| XSG0604000 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 6.0Vdc 4.0A 24.0W<br>ta:35°C, Class II |
| XSG0604000AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 6.0Vdc 4.0A 24.0W<br>ta:35°C, Class II |
| XSG0650300 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 6.5Vdc 0.3A 2.0W<br>ta:35°C, Class II  |
| XSG0650300AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 6.5Vdc 0.3A 2.0W<br>ta:35°C, Class II  |
| XSG0650400 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 6.5Vdc 0.4A 2.6W<br>ta:35°C, Class II  |
| XSG0650400AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 6.5Vdc 0.4A 2.6W<br>ta:35°C, Class II  |
| XSG0650500 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 6.5Vdc 0.5A 3.3W<br>ta:35°C, Class II  |
| XSG0650500AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 6.5Vdc 0.5A 3.3W<br>ta:35°C, Class II  |

R. A. Nill


For and on Behalf of  
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065, RECS accreditation under the Queensland Government legislative requirements and REAS accreditation under the NSW Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and Certificate verification, go to:

[www.saaapprovals.com.au](http://www.saaapprovals.com.au)

JAS-ANZ



[www.jas-anz.org/register](http://www.jas-anz.org/register)



Issued: 11-03-26 211085  
Renewed Page 7 of 45



A P P R O V A L S ®

## Certificate of Conformity/Approval

| Model           | Trade Name   | Rating/Marking                                                                        |
|-----------------|--------------|---------------------------------------------------------------------------------------|
| XSG0651000 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 6.5Vdc 1.0A 6.5W<br>ta:35°C, Class II  |
| XSG0651000AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 6.5Vdc 1.0A 6.5W<br>ta:35°C, Class II  |
| XSG0651500 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 6.5Vdc 1.5A 9.8W<br>ta:35°C, Class II  |
| XSG0651500AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 6.5Vdc 1.5A 9.8W<br>ta:35°C, Class II  |
| XSG0652000 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 6.5Vdc 2.0A 13.0W<br>ta:35°C, Class II |
| XSG0652000AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 6.5Vdc 2.0A 13.0W<br>ta:35°C, Class II |
| XSG0652500 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 6.5Vdc 2.5A 16.3W<br>ta:35°C, Class II |
| XSG0652500AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 6.5Vdc 2.5A 16.3W<br>ta:35°C, Class II |
| XSG0653000 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 6.5Vdc 3.0A 19.5W<br>ta:35°C, Class II |
| XSG0653000AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 6.5Vdc 3.0A 19.5W<br>ta:35°C, Class II |

R. A. Nill

For and on Behalf of  
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065, RECS accreditation under the Queensland Government legislative requirements and REAS accreditation under the NSW Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and Certificate verification, go to:

[www.saaapprovals.com.au](http://www.saaapprovals.com.au)



[www.jas-anz.org/register](http://www.jas-anz.org/register)



Issued: 11-03-26 211085  
Renewed Page 8 of 45



A P P R O V A L S ®

## Certificate of Conformity/Approval

| Model           | Trade Name   | Rating/Marking                                                                        |
|-----------------|--------------|---------------------------------------------------------------------------------------|
| XSG0653500 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 6.5Vdc 3.5A 22.8W<br>ta:35°C, Class II |
| XSG0653500AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 6.5Vdc 3.5A 22.8W<br>ta:35°C, Class II |
| XSG0730500 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 7.3Vdc 0.5A 3.7W<br>ta:35°C, Class II  |
| XSG0730500AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 7.3Vdc 0.5A 3.7W<br>ta:35°C, Class II  |
| XSG0731000 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 7.3Vdc 1.0A 7.3W<br>ta:35°C, Class II  |
| XSG0731000AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 7.3Vdc 1.0A 7.3W<br>ta:35°C, Class II  |
| XSG0731500 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 7.3Vdc 1.5A 11.0W<br>ta:35°C, Class II |
| XSG0731500AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 7.3Vdc 1.5A 11.0W<br>ta:35°C, Class II |
| XSG0732000 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 7.3Vdc 2.0A 14.6W<br>ta:35°C, Class II |
| XSG0732000AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 7.3Vdc 2.0A 14.6W<br>ta:35°C, Class II |

R. A. Nill

For and on Behalf of  
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065, RECS accreditation under the Queensland Government legislative requirements and REAS accreditation under the NSW Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and Certificate verification, go to:

[www.saaapprovals.com.au](http://www.saaapprovals.com.au)



[www.jas-anz.org/register](http://www.jas-anz.org/register)



Issued: 11-03-26 211085  
Renewed Page 9 of 45



A P P R O V A L S ®

## Certificate of Conformity/Approval

| Model           | Trade Name   | Rating/Marking                                                                        |
|-----------------|--------------|---------------------------------------------------------------------------------------|
| XSG0732500 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 7.3Vdc 2.5A 18.3W<br>ta:35°C, Class II |
| XSG0732500AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 7.3Vdc 2.5A 18.3W<br>ta:35°C, Class II |
| XSG0733000 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 7.3Vdc 3.0A 21.9W<br>ta:35°C, Class II |
| XSG0733000AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 7.3Vdc 3.0A 21.9W<br>ta:35°C, Class II |
| XSG0750500 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 7.5Vdc 0.5A 3.8W<br>ta:35°C, Class II  |
| XSG0750500AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 7.5Vdc 0.5A 3.8W<br>ta:35°C, Class II  |
| XSG0750800 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 7.5Vdc 0.8A 6.0W<br>ta:35°C, Class II  |
| XSG0750800AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 7.5Vdc 0.8A 6.0W<br>ta:35°C, Class II  |
| XSG0751000 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 7.5Vdc 1.0A 7.5W<br>ta:35°C, Class II  |
| XSG0751000AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 7.5Vdc 1.0A 7.5W<br>ta:35°C, Class II  |

R. A. Nill

For and on Behalf of  
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065, RECS accreditation under the Queensland Government legislative requirements and REAS accreditation under the NSW Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and Certificate verification, go to:

[www.saaapprovals.com.au](http://www.saaapprovals.com.au)



[www.jas-anz.org/register](http://www.jas-anz.org/register)



Issued: 11-03-26 211085  
Renewed Page 10 of 45



A P P R O V A L S ®

## Certificate of Conformity/Approval

| Model           | Trade Name   | Rating/Marking                                                                        |
|-----------------|--------------|---------------------------------------------------------------------------------------|
| XSG0751500 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 7.5Vdc 1.5A 11.3W<br>ta:35°C, Class II |
| XSG0751500AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 7.5Vdc 1.5A 11.3W<br>ta:35°C, Class II |
| XSG0752000 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 7.5Vdc 2.0A 15.0W<br>ta:35°C, Class II |
| XSG0752000AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 7.5Vdc 2.0A 15.0W<br>ta:35°C, Class II |
| XSG0752500 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 7.5Vdc 2.5A 18.8W<br>ta:35°C, Class II |
| XSG0752500AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 7.5Vdc 2.5A 18.8W<br>ta:35°C, Class II |
| XSG0753000 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 7.5Vdc 3.0A 22.5W<br>ta:35°C, Class II |
| XSG0753000AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 7.5Vdc 3.0A 22.5W<br>ta:35°C, Class II |
| XSG0840500 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 8.4Vdc 0.5A 4.2W<br>ta:35°C, Class II  |
| XSG0840500AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 8.4Vdc 0.5A 4.2W<br>ta:35°C, Class II  |

R. A. Nill

For and on Behalf of  
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065, RECS accreditation under the Queensland Government legislative requirements and REAS accreditation under the NSW Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and Certificate verification, go to:

[www.saaapprovals.com.au](http://www.saaapprovals.com.au)



[www.jas-anz.org/register](http://www.jas-anz.org/register)



Issued: 11-03-26 211085  
Renewed Page 11 of 45



A P P R O V A L S ®

## Certificate of Conformity/Approval

| Model           | Trade Name   | Rating/Marking                                                                        |
|-----------------|--------------|---------------------------------------------------------------------------------------|
| XSG0841000 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 8.4Vdc 1.0A 8.4W<br>ta:35°C, Class II  |
| XSG0841000AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 8.4Vdc 1.0A 8.4W<br>ta:35°C, Class II  |
| XSG0841200 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 8.4Vdc 1.2A 10.1W<br>ta:35°C, Class II |
| XSG0841200AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 8.4Vdc 1.2A 10.1W<br>ta:35°C, Class II |
| XSG0841500 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 8.4Vdc 1.5A 12.6W<br>ta:35°C, Class II |
| XSG0841500AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 8.4Vdc 1.5A 12.6W<br>ta:35°C, Class II |
| XSG0841800 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 8.4Vdc 1.8A 15.1W<br>ta:35°C, Class II |
| XSG0841800AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 8.4Vdc 1.8A 15.1W<br>ta:35°C, Class II |
| XSG0842000 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 8.4Vdc 2.0A 16.8W<br>ta:35°C, Class II |
| XSG0842000AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 8.4Vdc 2.0A 16.8W<br>ta:35°C, Class II |

R. A. Nill

For and on Behalf of  
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065, RECS accreditation under the Queensland Government legislative requirements and REAS accreditation under the NSW Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and Certificate verification, go to:

[www.saaapprovals.com.au](http://www.saaapprovals.com.au)



[www.jas-anz.org/register](http://www.jas-anz.org/register)



Issued: 11-03-26 211085  
Renewed Page 12 of 45



A P P R O V A L S ®

## Certificate of Conformity/Approval

| Model           | Trade Name   | Rating/Marking                                                                        |
|-----------------|--------------|---------------------------------------------------------------------------------------|
| XSG0842500 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 8.4Vdc 2.5 A21.0W<br>ta:35°C, Class II |
| XSG0842500AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 8.4Vdc 2.5A 21.0W<br>ta:35°C, Class II |
| XSG0843000 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 8.4Vdc 3.0A 25.2W<br>ta:35°C, Class II |
| XSG0843000AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 8.4Vdc 3.0A 25.2W<br>ta:35°C, Class II |
| XSG0900300 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 9.0Vdc 0.3A 2.7W<br>ta:35°C, Class II  |
| XSG0900300AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 9.0Vdc 0.3A 2.7W<br>ta:35°C, Class II  |
| XSG0900500 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 9.0Vdc 0.5A 4.5W<br>ta:35°C, Class II  |
| XSG0900500AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 9.0Vdc 0.5A 4.5W<br>ta:35°C, Class II  |
| XSG0900600 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 9.0Vdc 0.6A 5.4W<br>ta:35°C, Class II  |
| XSG0900600AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 9.0Vdc 0.6A 5.4W<br>ta:35°C, Class II  |

R. A. Nill


For and on Behalf of  
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065, RECS accreditation under the Queensland Government legislative requirements and REAS accreditation under the NSW Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and Certificate verification, go to:

[www.saaapprovals.com.au](http://www.saaapprovals.com.au)

JAS-ANZ



[www.jas-anz.org/register](http://www.jas-anz.org/register)



Issued: 11-03-26 211085  
Renewed Page 13 of 45



A P P R O V A L S ®

## Certificate of Conformity/Approval

| Model           | Trade Name   | Rating/Marking                                                                        |
|-----------------|--------------|---------------------------------------------------------------------------------------|
| XSG0901000 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 9.0Vdc 1.0A 9.0W<br>ta:35°C, Class II  |
| XSG0901000AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 9.0Vdc 1.0A 9.0W<br>ta:35°C, Class II  |
| XSG0901200 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 9.0Vdc 1.2A 10.8W<br>ta:35°C, Class II |
| XSG0901200AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 9.0Vdc 1.2A 10.8W<br>ta:35°C, Class II |
| XSG0901500 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 9.0Vdc 1.5A 13.5W<br>ta:35°C, Class II |
| XSG0901500AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 9.0Vdc 1.5A 13.5W<br>ta:35°C, Class II |
| XSG0902000 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 9.0Vdc 2.0A 18.0W<br>ta:35°C, Class II |
| XSG0902000AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 9.0Vdc 2.0A 18.0W<br>ta:35°C, Class II |
| XSG0902500 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 9.0Vdc 2.5A 22.5W<br>ta:35°C, Class II |
| XSG0902500AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 9.0Vdc 2.5A 22.5W<br>ta:35°C, Class II |

R. A. Nill

For and on Behalf of  
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065, RECS accreditation under the Queensland Government legislative requirements and REAS accreditation under the NSW Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and Certificate verification, go to:

[www.saaapprovals.com.au](http://www.saaapprovals.com.au)



[www.jas-anz.org/register](http://www.jas-anz.org/register)



Issued: 11-03-26 211085  
Renewed Page 14 of 45



A P P R O V A L S ®

## Certificate of Conformity/Approval

| Model           | Trade Name   | Rating/Marking                                                                         |
|-----------------|--------------|----------------------------------------------------------------------------------------|
| XSG1000500 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 10.0Vdc 0.5A 5.0W<br>ta:35°C, Class II  |
| XSG1000500AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 10.0Vdc 0.5A 5.0W<br>ta:35°C, Class II  |
| XSG1001000 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 10.0Vdc 1.0A 10.0W<br>ta:35°C, Class II |
| XSG1001000AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 10.0Vdc 1.0A 10.0W<br>ta:35°C, Class II |
| XSG1001500 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 10.0Vdc 1.5A 15.0W<br>ta:35°C, Class II |
| XSG1001500AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 10.0Vdc 1.5A 15.0W<br>ta:35°C, Class II |
| XSG1002000 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 10.0Vdc 2.0A 20.0W<br>ta:35°C, Class II |
| XSG1002000AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 10.0Vdc 2.0A 20.0W<br>ta:35°C, Class II |
| XSG1002500 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 10.0Vdc 2.5A 25.0W<br>ta:35°C, Class II |
| XSG1002500AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 10.0Vdc 2.5A 25.0W<br>ta:35°C, Class II |

R. A. Nill

For and on Behalf of  
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065, RECS accreditation under the Queensland Government legislative requirements and REAS accreditation under the NSW Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and Certificate verification, go to:

[www.saaapprovals.com.au](http://www.saaapprovals.com.au)



[www.jas-anz.org/register](http://www.jas-anz.org/register)



Issued: 11-03-26 211085  
Renewed Page 15 of 45



A P P R O V A L S ®

## Certificate of Conformity/Approval

| Model           | Trade Name   | Rating/Marking                                                                         |
|-----------------|--------------|----------------------------------------------------------------------------------------|
| XSG1100500 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 11.0Vdc 0.5A 5.5W<br>ta:35°C, Class II  |
| XSG1100500AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 11.0Vdc 0.5A 5.5W<br>ta:35°C, Class II  |
| XSG1101000 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 11.0Vdc 1.0A 11.0W<br>ta:35°C, Class II |
| XSG1101000AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 11.0Vdc 1.0A 11.0W<br>ta:35°C, Class II |
| XSG1101500 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 11.0Vdc 1.5A 16.5W<br>ta:35°C, Class II |
| XSG1101500AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 11.0Vdc 1.5A 16.5W<br>ta:35°C, Class II |
| XSG1102000 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 11.0Vdc 2.0A 22.0W<br>ta:35°C, Class II |
| XSG1102000AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 11.0Vdc 2.0A 22.0W<br>ta:35°C, Class II |
| XSG1102500 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 11.0Vdc 2.5A 27.5W<br>ta:35°C, Class II |
| XSG1102500AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 11.0Vdc 2.5A 27.5W<br>ta:35°C, Class II |

R. A. Nill

For and on Behalf of  
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065, RECS accreditation under the Queensland Government legislative requirements and REAS accreditation under the NSW Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and Certificate verification, go to:

[www.saaapprovals.com.au](http://www.saaapprovals.com.au)



[www.jas-anz.org/register](http://www.jas-anz.org/register)



Issued: 11-03-26 211085  
Renewed Page 16 of 45



A P P R O V A L S ®

## Certificate of Conformity/Approval

| Model           | Trade Name   | Rating/Marking                                                                         |
|-----------------|--------------|----------------------------------------------------------------------------------------|
| XSG1112700 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 11.1Vdc 2.7A 30.0W<br>ta:35°C, Class II |
| XSG1112700AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 11.1Vdc 2.7A 30.0W<br>ta:35°C, Class II |
| XSG1200300 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 12.0Vdc 0.3A 3.6W<br>ta:35°C, Class II  |
| XSG1200300AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 12.0Vdc 0.3A 3.6W<br>ta:35°C, Class II  |
| XSG1200400 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 12.0Vdc 0.4A 4.8W<br>ta:35°C, Class II  |
| XSG1200400AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 12.0Vdc 0.4A 4.8W<br>ta:35°C, Class II  |
| XSG1200500 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 12.0Vdc 0.5A 6.0W<br>ta:35°C, Class II  |
| XSG1200500AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 12.0Vdc 0.5A 6.0W<br>ta:35°C, Class II  |
| XSG1200600 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 12.0Vdc 0.6A 7.2W<br>ta:35°C, Class II  |
| XSG1200600AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 12.0Vdc 0.6A 7.2W<br>ta:35°C, Class II  |

R. A. Nill

For and on Behalf of  
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065, RECS accreditation under the Queensland Government legislative requirements and REAS accreditation under the NSW Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and Certificate verification, go to:

[www.saaapprovals.com.au](http://www.saaapprovals.com.au)



[www.jas-anz.org/register](http://www.jas-anz.org/register)



Issued: 11-03-26 211085  
Renewed Page 17 of 45



A P P R O V A L S ®

## Certificate of Conformity/Approval

| Model           | Trade Name   | Rating/Marking                                                                          |
|-----------------|--------------|-----------------------------------------------------------------------------------------|
| XSG1200700 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 12.0Vdc 0.7A 8.4W<br>ta:35°C, Class II   |
| XSG1200700AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 12.0Vdc 0.7A 8.4W<br>ta:35°C, Class II   |
| XSG1200800 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 12.0Vdc 0.8A 9.6W<br>ta:35°C, Class II   |
| XSG1200800AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 12.0Vdc 0.8A 9.6W<br>ta:35°C, Class II   |
| XSG1200900 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 12.0Vdc 0.9A 10.8W<br>ta:35°C, Class II  |
| XSG1200900AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 12.0Vdc 0.9A 10.8W<br>ta:35°C, Class II  |
| XSG1201000 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 12.0Vdc 1.0A 12.0W<br>ta:35°C, Class II  |
| XSG1201000AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 12.0Vdc 1.0A 12.0W<br>ta:35°C, Class II  |
| XSG1201250 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 12.0Vdc 1.25A 15.0W<br>ta:35°C, Class II |
| XSG1201250AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 12.0Vdc 1.25A 15.0W<br>ta:35°C, Class II |

R. A. Nill

For and on Behalf of  
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065, RECS accreditation under the Queensland Government legislative requirements and REAS accreditation under the NSW Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and Certificate verification, go to:

[www.saaapprovals.com.au](http://www.saaapprovals.com.au)



[www.jas-anz.org/register](http://www.jas-anz.org/register)



Issued: 11-03-26 211085  
Renewed Page 18 of 45



A P P R O V A L S ®

## Certificate of Conformity/Approval

| Model           | Trade Name   | Rating/Marking                                                                          |
|-----------------|--------------|-----------------------------------------------------------------------------------------|
| XSG1201500 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 12.0Vdc 1.5A 18.0W<br>ta:35°C, Class II  |
| XSG1201500AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 12.0Vdc 1.5A 18.0W<br>ta:35°C, Class II  |
| XSG1201750 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 12.0Vdc 1.75 A21.0W<br>ta:35°C, Class II |
| XSG1201750AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 12.0Vdc 1.75 A21.0W<br>ta:35°C, Class II |
| XSG1202000 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 12.0Vdc 2.0A 24.0W<br>ta:35°C, Class II  |
| XSG1202000AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 12.0Vdc 2.0A 24.0W<br>ta:35°C, Class II  |
| XSG1260500 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 12.6Vdc 0.5A 6.3W<br>ta:35°C, Class II   |
| XSG1260500AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 12.6Vdc 0.5A 6.3W<br>ta:35°C, Class II   |
| XSG1261000 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 12.6Vdc 1.0A 12.6W<br>ta:35°C, Class II  |
| XSG1261000AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 12.6Vdc 1.0A 12.6W<br>ta:35°C, Class II  |

R. A. Nill

For and on Behalf of  
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065, RECS accreditation under the Queensland Government legislative requirements and REAS accreditation under the NSW Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and Certificate verification, go to:

[www.saaapprovals.com.au](http://www.saaapprovals.com.au)



[www.jas-anz.org/register](http://www.jas-anz.org/register)



Issued: 11-03-26 211085  
Renewed Page 19 of 45



A P P R O V A L S ®

## Certificate of Conformity/Approval

| Model           | Trade Name   | Rating/Marking                                                                           |
|-----------------|--------------|------------------------------------------------------------------------------------------|
| XSG1261200 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 12.6Vdc 1.2A 15.1W<br>ta:35°C, Class II   |
| XSG1261200AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 12.6Vdc 1.2A 15.1W<br>ta:35°C, Class II   |
| XSG1261500 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 12.6Vdc 1.5A 18.9W<br>ta:35°C, Class II   |
| XSG1261500AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 12.6Vdc 1.5A 18.9W<br>ta:35°C, Class II   |
| XSG1261800 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 12.6Vdc 1.8A 22.7W<br>ta:35°C, Class II   |
| XSG1261800AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 12.6Vdc 1.8A 22.7W<br>ta:35°C, Class II   |
| XSG1262000 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 12.6Vdc 2.0A 25.2W<br>ta:35°C, Class II   |
| XSG1262000AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 12.6Vdc 2.0A 25.2W<br>ta:35°C, Class II   |
| XSG1282340 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 12.8Vdc 2.34A 29.95W<br>ta:35°C, Class II |
| XSG1282340AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 12.8Vdc 2.34A 29.95W<br>ta:35°C, Class II |

R. A. Nill


For and on Behalf of  
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065, RECS accreditation under the Queensland Government legislative requirements and REAS accreditation under the NSW Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and Certificate verification, go to:

[www.saaapprovals.com.au](http://www.saaapprovals.com.au)

JAS-ANZ



[www.jas-anz.org/register](http://www.jas-anz.org/register)



Issued: 11-03-26 211085  
Renewed Page 20 of 45



A P P R O V A L S ®

## Certificate of Conformity/Approval

| Model           | Trade Name   | Rating/Marking                                                                         |
|-----------------|--------------|----------------------------------------------------------------------------------------|
| XSG1300500 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 13.0Vdc 0.5A 6.5W<br>ta:35°C, Class II  |
| XSG1300500AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 13.0Vdc 0.5A 6.5W<br>ta:35°C, Class II  |
| XSG1301000 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 13.0Vdc 1.0A 13.0W<br>ta:35°C, Class II |
| XSG1301000AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 13.0Vdc 1.0A 13.0W<br>ta:35°C, Class II |
| XSG1301500 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 13.0Vdc 1.5A 19.5W<br>ta:35°C, Class II |
| XSG1301500AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 13.0Vdc 1.5A 19.5W<br>ta:35°C, Class II |
| XSG1302000 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 13.0Vdc 2.0A 26.0W<br>ta:35°C, Class II |
| XSG1302000AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 13.0Vdc 2.0A 26.0W<br>ta:35°C, Class II |
| XSG1350500 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 13.5Vdc 0.5A 6.8W<br>ta:35°C, Class II  |
| XSG1350500AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 13.5Vdc 0.5A 6.8W<br>ta:35°C, Class II  |

R. A. Nill

For and on Behalf of  
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065, RECS accreditation under the Queensland Government legislative requirements and REAS accreditation under the NSW Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and Certificate verification, go to:

[www.saaapprovals.com.au](http://www.saaapprovals.com.au)



[www.jas-anz.org/register](http://www.jas-anz.org/register)



Issued: 11-03-26 211085  
Renewed Page 21 of 45



A P P R O V A L S ®

## Certificate of Conformity/Approval

| Model           | Trade Name   | Rating/Marking                                                                         |
|-----------------|--------------|----------------------------------------------------------------------------------------|
| XSG1351000 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 13.5Vdc 1.0A 13.5W<br>ta:35°C, Class II |
| XSG1351000AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 13.5Vdc 1.0A 13.5W<br>ta:35°C, Class II |
| XSG1351500 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 13.5Vdc 1.5A 20.3W<br>ta:35°C, Class II |
| XSG1351500AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 13.5Vdc 1.5A 20.3W<br>ta:35°C, Class II |
| XSG1352000 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 13.5Vdc 2.0A 27.0W<br>ta:35°C, Class II |
| XSG1352000AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 13.5Vdc 2.0A 27.0W<br>ta:35°C, Class II |
| XSG1400500 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 14.0Vdc 0.5A 7.0W<br>ta:35°C, Class II  |
| XSG1400500AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 14.0Vdc 0.5A 7.0W<br>ta:35°C, Class II  |
| XSG1401000 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 14.0Vdc 1.0A 14.0W<br>ta:35°C, Class II |
| XSG1401000AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 14.0Vdc 1.0A 14.0W<br>ta:35°C, Class II |

R. A. Nill

For and on Behalf of  
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065, RECS accreditation under the Queensland Government legislative requirements and REAS accreditation under the NSW Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and Certificate verification, go to:

[www.saaapprovals.com.au](http://www.saaapprovals.com.au)



[www.jas-anz.org/register](http://www.jas-anz.org/register)



Issued: 11-03-26 211085  
Renewed Page 22 of 45



A P P R O V A L S ®

## Certificate of Conformity/Approval

| Model           | Trade Name   | Rating/Marking                                                                         |
|-----------------|--------------|----------------------------------------------------------------------------------------|
| XSG1401200 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 14.0Vdc 1.2A 16.8W<br>ta:35°C, Class II |
| XSG1401200AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 14.0Vdc 1.2A 16.8W<br>ta:35°C, Class II |
| XSG1401500 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 14.0Vdc 1.5A 21.0W<br>ta:35°C, Class II |
| XSG1401500AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 14.0Vdc 1.5A 21.0W<br>ta:35°C, Class II |
| XSG1402000 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 14.0Vdc 2.0A 28.0W<br>ta:35°C, Class II |
| XSG1402000AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 14.0Vdc 2.0A 28.0W<br>ta:35°C, Class II |
| XSG1460500 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 14.6Vdc 0.5A 7.3W<br>ta:35°C, Class II  |
| XSG1460500AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 14.6Vdc 0.5A 7.3W<br>ta:35°C, Class II  |
| XSG1460800 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 14.6Vdc 0.8A 11.7W<br>ta:35°C, Class II |
| XSG1460800AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 14.6Vdc 0.8A 11.7W<br>ta:35°C, Class II |

R. A. Nill

For and on Behalf of  
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065, RECS accreditation under the Queensland Government legislative requirements and REAS accreditation under the NSW Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and Certificate verification, go to:

[www.saaapprovals.com.au](http://www.saaapprovals.com.au)



[www.jas-anz.org/register](http://www.jas-anz.org/register)



Issued: 11-03-26 211085  
Renewed Page 23 of 45



A P P R O V A L S ®

## Certificate of Conformity/Approval

| Model           | Trade Name   | Rating/Marking                                                                          |
|-----------------|--------------|-----------------------------------------------------------------------------------------|
| XSG1461000 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 14.6Vdc 1.0A 14.6W<br>ta:35°C, Class II  |
| XSG1461000AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 14.6Vdc 1.0A 14.6W<br>ta:35°C, Class II  |
| XSG1461500 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 14.6Vdc 1.5A 21.9W<br>ta:35°C, Class II  |
| XSG1461500AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 14.6Vdc 1.5A 21.9W<br>ta:35°C, Class II  |
| XSG1461750 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 14.6Vdc 1.75A 25.6W<br>ta:35°C, Class II |
| XSG1461750AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 14.6Vdc 1.75A 25.6W<br>ta:35°C, Class II |
| XSG1500300 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 15.0Vdc 0.3A 4.5W<br>ta:35°C, Class II   |
| XSG1500300AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 15.0Vdc 0.3A 4.5W<br>ta:35°C, Class II   |
| XSG1500500 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 15.0Vdc 0.5A 7.5W<br>ta:35°C, Class II   |
| XSG1500500AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 15.0Vdc 0.5A 7.5W<br>ta:35°C, Class II   |

R. A. Nill

For and on Behalf of  
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065, RECS accreditation under the Queensland Government legislative requirements and REAS accreditation under the NSW Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and Certificate verification, go to:

[www.saaapprovals.com.au](http://www.saaapprovals.com.au)



[www.jas-anz.org/register](http://www.jas-anz.org/register)



Issued: 11-03-26 211085  
Renewed Page 24 of 45



A P P R O V A L S ®

## Certificate of Conformity/Approval

| Model           | Trade Name   | Rating/Marking                                                                          |
|-----------------|--------------|-----------------------------------------------------------------------------------------|
| XSG1500800 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 15.0Vdc 0.8A 12.0W<br>ta:35°C, Class II  |
| XSG1500800AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 15.0Vdc 0.8A 12.0W<br>ta:35°C, Class II  |
| XSG1501000 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 15.0Vdc 1.0A 15.0W<br>ta:35°C, Class II  |
| XSG1501000AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 15.0Vdc 1.0A 15.0W<br>ta:35°C, Class II  |
| XSG1501200 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 15.0Vdc 1.2A 18.0W<br>ta:35°C, Class II  |
| XSG1501200AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 15.0Vdc 1.2A 18.0W<br>ta:35°C, Class II  |
| XSG1501500 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 15.0Vdc 1.5A 22.5W<br>ta:35°C, Class II  |
| XSG1501500AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 15.0Vdc 1.5A 22.5W<br>ta:35°C, Class II  |
| XSG1501750 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 15.0Vdc 1.75A 26.3W<br>ta:35°C, Class II |
| XSG1501750AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 15.0Vdc 1.75A 26.3W<br>ta:35°C, Class II |

R. A. Nill

For and on Behalf of  
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065, RECS accreditation under the Queensland Government legislative requirements and REAS accreditation under the NSW Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and Certificate verification, go to:

[www.saaapprovals.com.au](http://www.saaapprovals.com.au)



[www.jas-anz.org/register](http://www.jas-anz.org/register)



Issued: 11-03-26 211085  
Renewed Page 25 of 45



A P P R O V A L S ®

## Certificate of Conformity/Approval

| Model           | Trade Name   | Rating/Marking                                                                         |
|-----------------|--------------|----------------------------------------------------------------------------------------|
| XSG1600500 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 16.0Vdc 0.5A 8.0W<br>ta:35°C, Class II  |
| XSG1600500AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 16.0Vdc 0.5A 8.0W<br>ta:35°C, Class II  |
| XSG1601000 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 16.0Vdc 1.0A 16.0W<br>ta:35°C, Class II |
| XSG1601000AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 16.0Vdc 1.0A 16.0W<br>ta:35°C, Class II |
| XSG1601500 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 16.0Vdc 1.5A 24.0W<br>ta:35°C, Class II |
| XSG1601500AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 16.0Vdc 1.5A 24.0W<br>ta:35°C, Class II |
| XSG1620500 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 16.2Vdc 0.5A 8.1W<br>ta:35°C, Class II  |
| XSG1620500AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 16.2Vdc 0.5A 8.1W<br>ta:35°C, Class II  |
| XSG1621000 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 16.2Vdc 1.0A 16.2W<br>ta:35°C, Class II |
| XSG1621000AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 16.2Vdc 1.0A 16.2W<br>ta:35°C, Class II |

R. A. Nill

For and on Behalf of  
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065, RECS accreditation under the Queensland Government legislative requirements and REAS accreditation under the NSW Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and Certificate verification, go to:

[www.saaapprovals.com.au](http://www.saaapprovals.com.au)



[www.jas-anz.org/register](http://www.jas-anz.org/register)



Issued: 11-03-26 211085  
Renewed Page 26 of 45



A P P R O V A L S ®

## Certificate of Conformity/Approval

| Model           | Trade Name   | Rating/Marking                                                                         |
|-----------------|--------------|----------------------------------------------------------------------------------------|
| XSG1621500 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 16.2Vdc 1.5A 24.3W<br>ta:35°C, Class II |
| XSG1621500AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 16.2Vdc 1.5A 24.3W<br>ta:35°C, Class II |
| XSG1680500 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 16.8Vdc 0.5A 8.4W<br>ta:35°C, Class II  |
| XSG1680500AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 16.8Vdc 0.5A 8.4W<br>ta:35°C, Class II  |
| XSG1681000 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 16.8Vdc 1.0A 16.8W<br>ta:35°C, Class II |
| XSG1681000AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 16.8Vdc 1.0A 16.8W<br>ta:35°C, Class II |
| XSG1681200 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 16.8Vdc 1.2A 20.2W<br>ta:35°C, Class II |
| XSG1681200AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 16.8Vdc 1.2A 20.2W<br>ta:35°C, Class II |
| XSG1681500 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 16.8Vdc 1.5A 25.2W<br>ta:35°C, Class II |
| XSG1681500AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 16.8Vdc 1.5A 25.2W<br>ta:35°C, Class II |

R. A. Nill

For and on Behalf of  
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065, RECS accreditation under the Queensland Government legislative requirements and REAS accreditation under the NSW Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and Certificate verification, go to:

[www.saaapprovals.com.au](http://www.saaapprovals.com.au)



[www.jas-anz.org/register](http://www.jas-anz.org/register)



Issued: 11-03-26 211085  
Renewed Page 27 of 45



A P P R O V A L S ®

## Certificate of Conformity/Approval

| Model           | Trade Name   | Rating/Marking                                                                         |
|-----------------|--------------|----------------------------------------------------------------------------------------|
| XSG1800500 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 18.0Vdc 0.5A 9.0W<br>ta:35°C, Class II  |
| XSG1800500AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 18.0Vdc 0.5A 9.0W<br>ta:35°C, Class II  |
| XSG1800600 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 18.0Vdc 0.6A 10.8W<br>ta:35°C, Class II |
| XSG1800600AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 18.0Vdc 0.6A 10.8W<br>ta:35°C, Class II |
| XSG1800700 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 18.0Vdc 0.7A 12.6W<br>ta:35°C, Class II |
| XSG1800700AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 18.0Vdc 0.7A 12.6W<br>ta:35°C, Class II |
| XSG1801000 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 18.0Vdc 1.0A 18.0W<br>ta:35°C, Class II |
| XSG1801000AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 18.0Vdc 1.0A 18.0W<br>ta:35°C, Class II |
| XSG1801500 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 18.0Vdc 1.5A 27.0W<br>ta:35°C, Class II |
| XSG1801500AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 18.0Vdc 1.5A 27.0W<br>ta:35°C, Class II |

R. A. Nill

For and on Behalf of  
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065, RECS accreditation under the Queensland Government legislative requirements and REAS accreditation under the NSW Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and Certificate verification, go to:

[www.saaapprovals.com.au](http://www.saaapprovals.com.au)



[www.jas-anz.org/register](http://www.jas-anz.org/register)



Issued: 11-03-26 211085  
Renewed Page 28 of 45



A P P R O V A L S ®

## Certificate of Conformity/Approval

| Model           | Trade Name   | Rating/Marking                                                                          |
|-----------------|--------------|-----------------------------------------------------------------------------------------|
| XSG1830500 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 18.3Vdc 0.5A 9.2W<br>ta:35°C, Class II   |
| XSG1830500AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 18.3Vdc 0.5A 9.2W<br>ta:35°C, Class II   |
| XSG1831000 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 18.3Vdc 1.0A 18.3W<br>ta:35°C, Class II  |
| XSG1831000AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 18.3Vdc 1.0A 18.3W<br>ta:35°C, Class II  |
| XSG1831250 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 18.3Vdc 1.25A 22.9W<br>ta:35°C, Class II |
| XSG1831250AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 18.3Vdc 1.25A 22.9W<br>ta:35°C, Class II |
| XSG1950500 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 19.5Vdc 0.5A 9.8W<br>ta:35°C, Class II   |
| XSG1950500AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 19.5Vdc 0.5A 9.8W<br>ta:35°C, Class II   |
| XSG1951000 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 19.5Vdc 1.0A 19.5W<br>ta:35°C, Class II  |
| XSG1951000AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 19.5Vdc 1.0A 19.5W<br>ta:35°C, Class II  |

R. A. Nill

For and on Behalf of  
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065, RECS accreditation under the Queensland Government legislative requirements and REAS accreditation under the NSW Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and Certificate verification, go to:

[www.saaapprovals.com.au](http://www.saaapprovals.com.au)



[www.jas-anz.org/register](http://www.jas-anz.org/register)



Issued: 11-03-26 211085  
Renewed Page 29 of 45



A P P R O V A L S ®

## Certificate of Conformity/Approval

| Model           | Trade Name   | Rating/Marking                                                                          |
|-----------------|--------------|-----------------------------------------------------------------------------------------|
| XSG1951250 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 19.5Vdc 1.25A 24.4W<br>ta:35°C, Class II |
| XSG1951250AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 19.5Vdc 1.25A 24.4W<br>ta:35°C, Class II |
| XSG2000500 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 20.0Vdc 0.5A 10.0W<br>ta:35°C, Class II  |
| XSG2000500AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 20.0Vdc 0.5A 10.0W<br>ta:35°C, Class II  |
| XSG2001000 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 20.0Vdc 1.0A 20.0W<br>ta:35°C, Class II  |
| XSG2001000AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 20.0Vdc 1.0A 20.0W<br>ta:35°C, Class II  |
| XSG2001250 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 20.0Vdc 1.25A 25.0W<br>ta:35°C, Class II |
| XSG2001250AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 20.0Vdc 1.25A 25.0W<br>ta:35°C, Class II |
| XSG2001500 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 20.0Vdc 1.5A 30.0W<br>ta:35°C, Class II  |
| XSG2001500AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 20.0Vdc 1.5A 30.0W<br>ta:35°C, Class II  |

R. A. Nill

For and on Behalf of  
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065, RECS accreditation under the Queensland Government legislative requirements and REAS accreditation under the NSW Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and Certificate verification, go to:

[www.saaapprovals.com.au](http://www.saaapprovals.com.au)



[www.jas-anz.org/register](http://www.jas-anz.org/register)



Issued: 11-03-26 211085  
Renewed Page 30 of 45



A P P R O V A L S ®

## Certificate of Conformity/Approval

| Model           | Trade Name   | Rating/Marking                                                                          |
|-----------------|--------------|-----------------------------------------------------------------------------------------|
| XSG2100500 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 21.0Vdc 0.5A 10.5W<br>ta:35°C, Class II  |
| XSG2100500AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 21.0Vdc 0.5A 10.5W<br>ta:35°C, Class II  |
| XSG2100600 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 21.0Vdc 0.6A 12.6W<br>ta:35°C, Class II  |
| XSG2100600AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 21.0Vdc 0.6A 12.6W<br>ta:35°C, Class II  |
| XSG2101000 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 21.0Vdc 1.0A 21.0W<br>ta:35°C, Class II  |
| XSG2101000AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 21.0Vdc 1.0A 21.0W<br>ta:35°C, Class II  |
| XSG2101200 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 21.0Vdc 1.2A 25.2W<br>ta:35°C, Class II  |
| XSG2101200AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 21.0Vdc 1.2A 25.2W<br>ta:35°C, Class II  |
| XSG2101420 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 21.0Vdc 1.42A 29.8W<br>ta:35°C, Class II |
| XSG2101420AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 21.0Vdc 1.42A 29.8W<br>ta:35°C, Class II |

R. A. Nill


For and on Behalf of  
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065, RECS accreditation under the Queensland Government legislative requirements and REAS accreditation under the NSW Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and Certificate verification, go to:

[www.saaapprovals.com.au](http://www.saaapprovals.com.au)

JAS-ANZ



[www.jas-anz.org/register](http://www.jas-anz.org/register)



Issued: 11-03-26 211085  
Renewed Page 31 of 45



A P P R O V A L S ®

## Certificate of Conformity/Approval

| Model           | Trade Name   | Rating/Marking                                                                         |
|-----------------|--------------|----------------------------------------------------------------------------------------|
| XSG2200500 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 22.0Vdc 0.5A 11.0W<br>ta:35°C, Class II |
| XSG2200500AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 22.0Vdc 0.5A 11.0W<br>ta:35°C, Class II |
| XSG2201000 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 22.0Vdc 1.0A 22.0W<br>ta:35°C, Class II |
| XSG2201000AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 22.0Vdc 1.0A 22.0W<br>ta:35°C, Class II |
| XSG2201200 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 22.0Vdc 1.2A 26.4W<br>ta:35°C, Class II |
| XSG2201200AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 22.0Vdc 1.2A 26.4W<br>ta:35°C, Class II |
| XSG2250500 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 22.5Vdc 0.5A 11.3W<br>ta:35°C, Class II |
| XSG2250500AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 22.5Vdc 0.5A 11.3W<br>ta:35°C, Class II |
| XSG2250600 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 22.5Vdc 0.6A 13.5W<br>ta:35°C, Class II |
| XSG2250600AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 22.5Vdc 0.6A 13.5W<br>ta:35°C, Class II |

R. A. Nill

For and on Behalf of  
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065, RECS accreditation under the Queensland Government legislative requirements and REAS accreditation under the NSW Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and Certificate verification, go to:

[www.saaapprovals.com.au](http://www.saaapprovals.com.au)



[www.jas-anz.org/register](http://www.jas-anz.org/register)



Issued: 11-03-26 211085  
Renewed Page 32 of 45



A P P R O V A L S ®

## Certificate of Conformity/Approval

| Model           | Trade Name   | Rating/Marking                                                                         |
|-----------------|--------------|----------------------------------------------------------------------------------------|
| XSG2250800 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 22.5Vdc 0.8A 18.0W<br>ta:35°C, Class II |
| XSG2250800AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 22.5Vdc 0.8A 18.0W<br>ta:35°C, Class II |
| XSG2251000 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 22.5Vdc 1.0A 22.5W<br>ta:35°C, Class II |
| XSG2251000AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 22.5Vdc 1.0A 22.5W<br>ta:35°C, Class II |
| XSG2251200 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 22.5Vdc 1.2A 27.0W<br>ta:35°C, Class II |
| XSG2251200AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 22.5Vdc 1.2A 27.0W<br>ta:35°C, Class II |
| XSG2400300 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 24.0Vdc 0.3A 7.2W<br>ta:35°C, Class II  |
| XSG2400300AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 24.0Vdc 0.3A 7.2W<br>ta:35°C, Class II  |
| XSG2400380 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 24.0Vdc 0.38A 9.1W<br>ta:35°C, Class II |
| XSG2400380AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 24.0Vdc 0.38A 9.1W<br>ta:35°C, Class II |

R. A. Nill

For and on Behalf of  
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065, RECS accreditation under the Queensland Government legislative requirements and REAS accreditation under the NSW Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and Certificate verification, go to:

[www.saaapprovals.com.au](http://www.saaapprovals.com.au)



[www.jas-anz.org/register](http://www.jas-anz.org/register)



Issued: 11-03-26 211085  
Renewed Page 33 of 45



A P P R O V A L S ®

## Certificate of Conformity/Approval

| Model           | Trade Name   | Rating/Marking                                                                         |
|-----------------|--------------|----------------------------------------------------------------------------------------|
| XSG2400500 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 24.0Vdc 0.5A 12.0W<br>ta:35°C, Class II |
| XSG2400500AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 24.0Vdc 0.5A 12.0W<br>ta:35°C, Class II |
| XSG2400600 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 24.0Vdc 0.6A 14.4W<br>ta:35°C, Class II |
| XSG2400600AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 24.0Vdc 0.6A 14.4W<br>ta:35°C, Class II |
| XSG2400800 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 24.0Vdc 0.8A 19.2W<br>ta:35°C, Class II |
| XSG2400800AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 24.0Vdc 0.8A 19.2W<br>ta:35°C, Class II |
| XSG2401000 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 24.0Vdc 1.0A 24.0W<br>ta:35°C, Class II |
| XSG2401000AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 24.0Vdc 1.0A 24.0W<br>ta:35°C, Class II |
| XSG2401200 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 24.0Vdc 1.2A 28.8W<br>ta:35°C, Class II |
| XSG2401200AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 24.0Vdc 1.2A 28.8W<br>ta:35°C, Class II |

R. A. Nill

For and on Behalf of  
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065, RECS accreditation under the Queensland Government legislative requirements and REAS accreditation under the NSW Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and Certificate verification, go to:

[www.saaapprovals.com.au](http://www.saaapprovals.com.au)



[www.jas-anz.org/register](http://www.jas-anz.org/register)



Issued: 11-03-26 211085  
Renewed Page 34 of 45



A P P R O V A L S ®

## Certificate of Conformity/Approval

| Model           | Trade Name   | Rating/Marking                                                                          |
|-----------------|--------------|-----------------------------------------------------------------------------------------|
| XSG2401250 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 24.0Vdc 1.25A 30.0W<br>ta:35°C, Class II |
| XSG2401250AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 24.0Vdc 1.25A 30.0W<br>ta:35°C, Class II |
| XSG2520500 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 25.2Vdc 0.5A 12.6W<br>ta:35°C, Class II  |
| XSG2520500AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 25.2Vdc 0.5A 12.6W<br>ta:35°C, Class II  |
| XSG2521000 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 25.2Vdc 1.0A 25.2W<br>ta:35°C, Class II  |
| XSG2521000AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 25.2Vdc 1.0A 25.2W<br>ta:35°C, Class II  |
| XSG2550500 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 25.5Vdc 0.5A 12.8W<br>ta:35°C, Class II  |
| XSG2550500AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 25.5Vdc 0.5A 12.8W<br>ta:35°C, Class II  |
| XSG2551000 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 25.5Vdc 1.0A 25.5W<br>ta:35°C, Class II  |
| XSG2551000AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 25.5Vdc 1.0A 25.5W<br>ta:35°C, Class II  |

R. A. Nill

For and on Behalf of  
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065, RECS accreditation under the Queensland Government legislative requirements and REAS accreditation under the NSW Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and Certificate verification, go to:

[www.saaapprovals.com.au](http://www.saaapprovals.com.au)



[www.jas-anz.org/register](http://www.jas-anz.org/register)



Issued: 11-03-26 211085  
Renewed Page 35 of 45



A P P R O V A L S ®

## Certificate of Conformity/Approval

| Model           | Trade Name   | Rating/Marking                                                                         |
|-----------------|--------------|----------------------------------------------------------------------------------------|
| XSG2700500 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 27.0Vdc 0.5A 13.5W<br>ta:35°C, Class II |
| XSG2700500AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 27.0Vdc 0.5A 13.5W<br>ta:35°C, Class II |
| XSG2701000 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 27.0Vdc 1.0A 27.0W<br>ta:35°C, Class II |
| XSG2701000AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 27.0Vdc 1.0A 27.0W<br>ta:35°C, Class II |
| XSG2800500 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 28.0Vdc 0.5A 14.0W<br>ta:35°C, Class II |
| XSG2800500AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 28.0Vdc 0.5A 14.0W<br>ta:35°C, Class II |
| XSG2801000 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 28.0Vdc 1.0A 28.0W<br>ta:35°C, Class II |
| XSG2801000AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 28.0Vdc 1.0A 28.0W<br>ta:35°C, Class II |
| XSG2900500 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 29.0Vdc 0.5A 14.5W<br>ta:35°C, Class II |
| XSG2900500AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 29.0Vdc 0.5A 14.5W<br>ta:35°C, Class II |

R. A. Nill

For and on Behalf of  
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065, RECS accreditation under the Queensland Government legislative requirements and REAS accreditation under the NSW Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and Certificate verification, go to:

[www.saaapprovals.com.au](http://www.saaapprovals.com.au)



[www.jas-anz.org/register](http://www.jas-anz.org/register)



Issued: 11-03-26 211085  
Renewed Page 36 of 45



A P P R O V A L S ®

## Certificate of Conformity/Approval

| Model           | Trade Name   | Rating/Marking                                                                         |
|-----------------|--------------|----------------------------------------------------------------------------------------|
| XSG2901000 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 29.0Vdc 1.0A 29.0W<br>ta:35°C, Class II |
| XSG2901000AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 29.0Vdc 1.0A 29.0W<br>ta:35°C, Class II |
| XSG2920300 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 29.2Vdc 0.3A 8.8W<br>ta:35°C, Class II  |
| XSG2920300AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 29.2Vdc 0.3A 8.8W<br>ta:35°C, Class II  |
| XSG2920400 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 29.2Vdc 0.4A 11.7W<br>ta:35°C, Class II |
| XSG2920400AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 29.2Vdc 0.4A 11.7W<br>ta:35°C, Class II |
| XSG2920500 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 29.2Vdc 0.5A 14.6W<br>ta:35°C, Class II |
| XSG2920500AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 29.2Vdc 0.5A 14.6W<br>ta:35°C, Class II |
| XSG2921000 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 29.2Vdc 1.0A 29.2W<br>ta:35°C, Class II |
| XSG2921000AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 29.2Vdc 1.0A 29.2W<br>ta:35°C, Class II |

R. A. Nill

For and on Behalf of  
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065, RECS accreditation under the Queensland Government legislative requirements and REAS accreditation under the NSW Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and Certificate verification, go to:

[www.saaapprovals.com.au](http://www.saaapprovals.com.au)



[www.jas-anz.org/register](http://www.jas-anz.org/register)



Issued: 11-03-26 211085  
Renewed Page 37 of 45



A P P R O V A L S ®

## Certificate of Conformity/Approval

| Model           | Trade Name   | Rating/Marking                                                                         |
|-----------------|--------------|----------------------------------------------------------------------------------------|
| XSG2940500 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 29.4Vdc 0.5A 14.7W<br>ta:35°C, Class II |
| XSG2940500AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 29.4Vdc 0.5A 14.7W<br>ta:35°C, Class II |
| XSG2941000 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 29.4Vdc 1.0A 29.4W<br>ta:35°C, Class II |
| XSG2941000AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 29.4Vdc 1.0A 29.4W<br>ta:35°C, Class II |
| XSG3000500 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 30.0Vdc 0.5A 15.0W<br>ta:35°C, Class II |
| XSG3000500AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 30.0Vdc 0.5A 15.0W<br>ta:35°C, Class II |
| XSG3001000 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 30.0Vdc 1.0A 30.0W<br>ta:35°C, Class II |
| XSG3001000AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 30.0Vdc 1.0A 30.0W<br>ta:35°C, Class II |
| XSG3200500 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 32.0Vdc 0.5A 16.0W<br>ta:35°C, Class II |
| XSG3200500AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 32.0Vdc 0.5A 16.0W<br>ta:35°C, Class II |

R. A. Nill

For and on Behalf of  
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065, RECS accreditation under the Queensland Government legislative requirements and REAS accreditation under the NSW Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and Certificate verification, go to:

[www.saaapprovals.com.au](http://www.saaapprovals.com.au)



[www.jas-anz.org/register](http://www.jas-anz.org/register)



Issued: 11-03-26 211085  
Renewed Page 38 of 45



A P P R O V A L S ®

## Certificate of Conformity/Approval

| Model           | Trade Name   | Rating/Marking                                                                         |
|-----------------|--------------|----------------------------------------------------------------------------------------|
| XSG3200900 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 32.0Vdc 0.9A 28.8W<br>ta:35°C, Class II |
| XSG3200900AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 32.0Vdc 0.9A 28.8W<br>ta:35°C, Class II |
| XSG3300500 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 33.0Vdc 0.5A 16.5W<br>ta:35°C, Class II |
| XSG3300500AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 33.0Vdc 0.5A 16.5W<br>ta:35°C, Class II |
| XSG3300800 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 33.0Vdc 0.8A 26.4W<br>ta:35°C, Class II |
| XSG3300800AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 33.0Vdc 0.8A 26.4W<br>ta:35°C, Class II |
| XSG3300900 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 33.0Vdc 0.9A 29.7W<br>ta:35°C, Class II |
| XSG3300900AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 33.0Vdc 0.9A 29.7W<br>ta:35°C, Class II |
| XSG3360500 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 33.6Vdc 0.5A 16.8W<br>ta:35°C, Class II |
| XSG3360500AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 33.6Vdc 0.5A 16.8W<br>ta:35°C, Class II |

R. A. Nill

For and on Behalf of  
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065, RECS accreditation under the Queensland Government legislative requirements and REAS accreditation under the NSW Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and Certificate verification, go to:

[www.saaapprovals.com.au](http://www.saaapprovals.com.au)



[www.jas-anz.org/register](http://www.jas-anz.org/register)



Issued: 11-03-26 211085  
Renewed Page 39 of 45



A P P R O V A L S ®

## Certificate of Conformity/Approval

| Model           | Trade Name   | Rating/Marking                                                                         |
|-----------------|--------------|----------------------------------------------------------------------------------------|
| XSG3360800 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 33.6Vdc 0.8A 26.9W<br>ta:35°C, Class II |
| XSG3360800AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 33.6Vdc 0.8A 26.9W<br>ta:35°C, Class II |
| XSG3400500 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 34.0Vdc 0.5A 17.0W<br>ta:35°C, Class II |
| XSG3400500AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 34.0Vdc 0.5A 17.0W<br>ta:35°C, Class II |
| XSG3400800 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 34.0Vdc 0.8A 27.2W<br>ta:35°C, Class II |
| XSG3400800AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 34.0Vdc 0.8A 27.2W<br>ta:35°C, Class II |
| XSG3500500 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 35.0Vdc 0.5A 17.5W<br>ta:35°C, Class II |
| XSG3500500AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 35.0Vdc 0.5A 17.5W<br>ta:35°C, Class II |
| XSG3500800 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 35.0Vdc 0.8A 28.0W<br>ta:35°C, Class II |
| XSG3500800AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 35.0Vdc 0.8A 28.0W<br>ta:35°C, Class II |

R. A. Nill

For and on Behalf of  
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065, RECS accreditation under the Queensland Government legislative requirements and REAS accreditation under the NSW Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and Certificate verification, go to:

[www.saaapprovals.com.au](http://www.saaapprovals.com.au)



[www.jas-anz.org/register](http://www.jas-anz.org/register)



Issued: 11-03-26 211085  
Renewed Page 40 of 45



A P P R O V A L S ®

## Certificate of Conformity/Approval

| Model           | Trade Name   | Rating/Marking                                                                         |
|-----------------|--------------|----------------------------------------------------------------------------------------|
| XSG3600300 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 36.0Vdc 0.3A 10.8W<br>ta:35°C, Class II |
| XSG3600300AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 36.0Vdc 0.3A 10.8W<br>ta:35°C, Class II |
| XSG3600500 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 36.0Vdc 0.5A 18.0W<br>ta:35°C, Class II |
| XSG3600500AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 36.0Vdc 0.5A 18.0W<br>ta:35°C, Class II |
| XSG3600800 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 36.0Vdc 0.8A 28.8W<br>ta:35°C, Class II |
| XSG3600800AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 36.0Vdc 0.8A 28.8W<br>ta:35°C, Class II |
| XSG3780500 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 37.8Vdc 0.5A 18.9W<br>ta:35°C, Class II |
| XSG3780500AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 37.8Vdc 0.5A 18.9W<br>ta:35°C, Class II |
| XSG3780700 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 37.8Vdc 0.7A 26.5W<br>ta:35°C, Class II |
| XSG3780700AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 37.8Vdc 0.7A 26.5W<br>ta:35°C, Class II |

R. A. Nill

For and on Behalf of  
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065, RECS accreditation under the Queensland Government legislative requirements and REAS accreditation under the NSW Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and Certificate verification, go to:

[www.saaapprovals.com.au](http://www.saaapprovals.com.au)



[www.jas-anz.org/register](http://www.jas-anz.org/register)



Issued: 11-03-26 211085  
Renewed Page 41 of 45



A P P R O V A L S ®

## Certificate of Conformity/Approval

| Model           | Trade Name   | Rating/Marking                                                                         |
|-----------------|--------------|----------------------------------------------------------------------------------------|
| XSG4020500 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 40.2Vdc 0.5A 20.1W<br>ta:35°C, Class II |
| XSG4020500AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 40.2Vdc 0.5A 20.1W<br>ta:35°C, Class II |
| XSG4020700 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 40.2Vdc 0.7A 28.1W<br>ta:35°C, Class II |
| XSG4020700AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 40.2Vdc 0.7A 28.1W<br>ta:35°C, Class II |
| XSG4200500 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 42.0Vdc 0.5A 21.0W<br>ta:35°C, Class II |
| XSG4200500AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 42.0Vdc 0.5A 21.0W<br>ta:35°C, Class II |
| XSG4200700 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 42.0Vdc 0.7A 29.4W<br>ta:35°C, Class II |
| XSG4200700AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 42.0Vdc 0.7A 29.4W<br>ta:35°C, Class II |
| XSG4250500 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 42.5Vdc 0.5A 21.3W<br>ta:35°C, Class II |
| XSG4250500AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 42.5Vdc 0.5A 21.3W<br>ta:35°C, Class II |

R. A. Nill


For and on Behalf of  
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065, RECS accreditation under the Queensland Government legislative requirements and REAS accreditation under the NSW Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and Certificate verification, go to:

[www.saaapprovals.com.au](http://www.saaapprovals.com.au)

JAS-ANZ



[www.jas-anz.org/register](http://www.jas-anz.org/register)



Issued: 11-03-26 211085  
Renewed Page 42 of 45



A P P R O V A L S ®

## Certificate of Conformity/Approval

| Model           | Trade Name   | Rating/Marking                                                                         |
|-----------------|--------------|----------------------------------------------------------------------------------------|
| XSG4250700 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 42.5Vdc 0.7A 29.8W<br>ta:35°C, Class II |
| XSG4250700AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 42.5Vdc 0.7A 29.8W<br>ta:35°C, Class II |
| XSG4300500 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 43.0Vdc 0.5A 21.5W<br>ta:35°C, Class II |
| XSG4300500AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 43.0Vdc 0.5A 21.5W<br>ta:35°C, Class II |
| XSG4300600 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 43.0Vdc 0.6A 25.8W<br>ta:35°C, Class II |
| XSG4300600AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 43.0Vdc 0.6A 25.8W<br>ta:35°C, Class II |
| XSG4380500 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 43.8Vdc 0.5A 21.9W<br>ta:35°C, Class II |
| XSG4380500AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 43.8Vdc 0.5A 21.9W<br>ta:35°C, Class II |
| XSG4380600 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 43.8Vdc 0.6A 26.3W<br>ta:35°C, Class II |
| XSG4380600AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 43.8Vdc 0.6A 26.3W<br>ta:35°C, Class II |

R. A. Nill

For and on Behalf of  
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065, RECS accreditation under the Queensland Government legislative requirements and REAS accreditation under the NSW Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and Certificate verification, go to:

[www.saaapprovals.com.au](http://www.saaapprovals.com.au)



[www.jas-anz.org/register](http://www.jas-anz.org/register)



Issued: 11-03-26 211085  
Renewed Page 43 of 45



A P P R O V A L S ®

## Certificate of Conformity/Approval

| Model           | Trade Name   | Rating/Marking                                                                         |
|-----------------|--------------|----------------------------------------------------------------------------------------|
| XSG4400500 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 44.0Vdc 0.5A 22.0W<br>ta:35°C, Class II |
| XSG4400500AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 44.0Vdc 0.5A 22.0W<br>ta:35°C, Class II |
| XSG4400600 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 44.0Vdc 0.6A 26.4W<br>ta:35°C, Class II |
| XSG4400600AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 44.0Vdc 0.6A 26.4W<br>ta:35°C, Class II |
| XSG4500500 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 45.0Vdc 0.5A 22.5W<br>ta:35°C, Class II |
| XSG4500500AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 45.0Vdc 0.5A 22.5W<br>ta:35°C, Class II |
| XSG4600600 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 46.0Vdc 0.6A 27.6W<br>ta:35°C, Class II |
| XSG4600600AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 46.0Vdc 0.6A 27.6W<br>ta:35°C, Class II |
| XSG4620500 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 46.2Vdc 0.5A 23.1W<br>ta:35°C, Class II |
| XSG4620500AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 46.2Vdc 0.5A 23.1W<br>ta:35°C, Class II |

R. A. Nill

For and on Behalf of  
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065, RECS accreditation under the Queensland Government legislative requirements and REAS accreditation under the NSW Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and Certificate verification, go to:

[www.saaapprovals.com.au](http://www.saaapprovals.com.au)



[www.jas-anz.org/register](http://www.jas-anz.org/register)



Issued: 11-03-26 211085  
Renewed Page 44 of 45



A P P R O V A L S ®

## Certificate of Conformity/Approval

| Model           | Trade Name   | Rating/Marking                                                                           |
|-----------------|--------------|------------------------------------------------------------------------------------------|
| XSG4620600 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 46.2Vdc 0.6A 27.7W<br>ta:35°C, Class II   |
| XSG4620600AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 46.2Vdc 0.6A 27.7W<br>ta:35°C, Class II   |
| XSG4800300 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 48.0Vdc 0.3A 14.4W<br>ta:35°C, Class II   |
| XSG4800300AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 48.0Vdc 0.3A 14.4W<br>ta:35°C, Class II   |
| XSG4800500 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 48.0Vdc 0.5A 24.0W<br>ta:35°C, Class II   |
| XSG4800500AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 48.0Vdc 0.5A 24.0W<br>ta:35°C, Class II   |
| XSG4800600 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 48.0Vdc 0.6A 28.8W<br>ta:35°C, Class II   |
| XSG4800600AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 48.0Vdc 0.6A 28.8W<br>ta:35°C, Class II   |
| XSG4800625 L3   | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 48.0Vdc 0.625A 30.0W<br>ta:35°C, Class II |
| XSG4800625AU L3 | Xinsu Global | Input: 100-240Vac 50/60Hz, 0.6A Max<br>Output: 48.0Vdc 0.625A 30.0W<br>ta:35°C, Class II |

R. A. Nill


For and on Behalf of  
SAA Approvals Pty Ltd

This certificate is issued by SAA Approvals Pty Ltd in accordance with the SAA Approvals Electrical Product Safety Certification Scheme accredited by JAS-ANZ under AS/NZS ISO/IEC 17065, RECS accreditation under the Queensland Government legislative requirements and REAS accreditation under the NSW Government legislative requirements. SAA certifies the product nominated in this certificate complies with standard/s listed above in accordance with the schemes herein.

For SAA Contact Details and Certificate verification, go to:

[www.saaapprovals.com.au](http://www.saaapprovals.com.au)

JAS-ANZ



[www.jas-anz.org/register](http://www.jas-anz.org/register)



Issued: 11-03-26 211085  
Renewed Page 45 of 45