

This authorizes the application of the Certification Mark(s) shown below to the models described in the Product(s) Covered section when made in accordance with the conditions set forth in the Certification Agreement and Listing Report. This authorization also applies to multiple listee model(s) identified on the correlation page of the Listing Report.

This document is the property of Intertek Testing Services and is not transferable. The certification mark(s) may be applied only at the location of the Party Authorized To Apply Mark.

Applicant:	Xinsu Global Electronic Co., Limited	Manufacturer:	Xinsu Global Electronic Co., Limited
Address:	Unit 2508A 25IF Bank of America Tower 12 HARCOURT ROAD CENTRAL Hong Kong SAR	Address:	3rd Floor, No. 1 Building, C district, 108 Honghu Road, Yanluo Street, Baoan District, SHENZHEN, Guangdong 518127
Country:	CHINA	Country:	CHINA
Party Authorized To Apply Mark:	Same as Manufacturer		
Report Issuing Office:	Intertek Testing Services Shenzhen Limited Longhua Branch		
Control Number:	<u>5024971</u>	Authorized by:	 for L. Matthew Snyder, Certification Manager



This document supersedes all previous Authorizations to Mark for the noted Report Number.

This Authorization to Mark is for the exclusive use of Intertek's Client and is provided pursuant to the Certification agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Authorization to Mark. Only the Client is authorized to permit copying or distribution of this Authorization to Mark and then only in its entirety. Use of Intertek's Certification mark is restricted to the conditions laid out in the agreement and in this Authorization to Mark. Any further use of the Intertek name for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. Initial Factory Assessments and Follow up Services are for the purpose of assuring appropriate usage of the Certification mark in accordance with the agreement, they are not for the purposes of production quality control and do not relieve the Client of their obligations in this respect.

Intertek Testing Services NA Inc.
545 East Algonquin Road, Arlington Heights, IL 60005
Telephone 800-345-3851 or 847-439-5667 Fax 312-283-1672

Standard(s):	Audio/Video, Information and Communication Technology Equipment - Part 1: Safety Requirements [UL 62368-1:2019 Ed.3+R:22Oct2021] Audio/Video, Information and Communication Technology Equipment - Part 1: Safety Requirements [CSA C22.2#62368-1:2019 Ed.3+U1]
Product:	SWITCHING POWER SUPPLY, CHARGER
Brand Name:	
Models:	XSG, XSE or XSEC; followed by seven numbers; may be followed by US. XSG, XSE or XSEC; followed by seven numbers; followed by US; followed by two characters; followed by L1. XSG, XSE or XSEC; followed by seven numbers; followed by two characters; followed by L1.

2.0 Product Description	
Product	SWITCHING POWER SUPPLY, CHARGER
Brand name	
Description	The product covered by this report is SWITCHING POWER SUPPLY or CHARGER, intended for Audio/Video, Information And Communication Technology Equipment use. It is a direct plug-in or desk top equipment for indoor use only, using at overvoltage category II and pollution degree 2. Operating environment temperature: 35°C Maximum altitude: 5000m
Models	XSG, XSE or XSEC; followed by seven numbers; may be followed by US. XSG, XSE or XSEC; followed by seven numbers; followed by US; followed by two characters; followed by L1. XSG, XSE or XSEC; followed by seven numbers; followed by two characters; followed by L1.
Model Similarity	All models are identical to each other except for model number, shape, size, PCB Layout, output rating, secondary windings of transformer and some secondary components to adjust output rating; Refer to Illustration 8 of section 7.0 for details.
Ratings	Input:100-240VAC, 50/60Hz, 1.3A Max, Class II Output: 3.0-48.0VDC, 0.10-5.00A, 40.0W Max
Other Ratings	NA