



FCC Part 15 SDOC Supplier's Declaration of Conformity

This Certificate of Conformity is hereby issued to the product designated below:

Certificate No......: 25EP060200F02
Report No......: EP25060200F02
Date Issue......: 2026-03-25
Applicant's name: Xinsu Global Electronic Co., Limited
Address.....: Unit 2508A, 25/F Bank Of America Tower, 12 Harcourt Road, Central,
HONG KONG
Manufacturer's name.....: Xinsu Global Electronic Co., Limited
Address.....: Unit 2508A, 25/F Bank Of America Tower, 12 Harcourt Road, Central,
HONG KONG
Product Description: SWITCHING POWER SUPPLY/CHARGER
Model(s)/Type References : XSG*****US, XSG*****US L1, XSG***** , XSG***** L1,
XSE***** , XSE***** L1, XSEC***** , XSEC***** L1,
XSE*****US, XSE*****US L1, XSEC*****US, XSEC*****US L1
(***** are variables, see appendix for details)
Parameters: Input: 100-240VAC, 50/60Hz, 1.3A Max
Output: See appendix for details
Standard(s): FCC Part 15 Subpart B
ANSI C63.4:2014

The device bearing the trade name and model specified above has been shown to comply with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified. (Refer to Test Report if any modifications were made for compliance).

This certificate of conformity is based on a single evaluation of the submitted sample(s) of the above mentioned product. It does not imply an assessment of the whole production have to be observed.

Approved By



Eric Liu
Director of engineering department



FCC Part 15 SDOC Supplier's Declaration of Conformity

Appendix of Certificate No.: 25EP060200F02


Model list:

Model No.	Rated output voltage (VDC)	Rated output current (A)	Maximum rated output power (W)	Transformer
XSG*****US , XSG*****US L1,	3.0-7.9	0.10-5.00	25.0	TR-036B-05A
XSG***** , XSG***** L1,	8.0-9.0	0.10-4.00	36.0	TR-036B-12A
XSE***** , XSE***** L1,	9.1-12.6	0.10-3.00	37.8	
XSEC***** , XSEC***** L1,	12.7-17.0	0.10-2.50	39.6	
XSE*****US , XSE*****US L1,	17.1-30.0	0.10-2.00	40.0	TR-036B-24A
XSEC*****US , XSEC*****US L1	30.1-48.0	0.10-1.32	40.0	TR-036B-36A

Remark:

The 1st to 3rd "*" can be replaced by three digits from 030 to 480, indicate output voltage range from 3.0-48.0Vdc the minimum rising step by 0.1V, eg. 030=3.0V, 480=48.0V;

The 4th to 7th "*" can be replaced by four digits from 0100 to 5000, indicate output current range from 0.10-5.00A, the minimum rising step by 0.01A, eg. 0100=0.10A, 5000=5.00A.



Dongguan Pubiao Testing Technology Co., Ltd

Room 101, Building 1, No.30, Minghua Road, Shijie, Shijie Town, Dongguan, Guangdong, China.

Tel: +86 769 81813516 E-mail: service@pubiaotest.com Web: www.pubiaotest.com